

# SAFETY DATA SHEET

AMAZON ENVIRONMENTAL. INC.  
7180 Commerce Circle  
Fridley, MN 55432  
DATE OF PREPARATION: 09/25/15

EMERGENCY TELEPHONE NUMBER:  
1-800-262-8200 CHEMTREC  
INFORMATION TELEPHONE NUMBER:  
(763)-572-0800

## SECTION 1 -PRODUCT IDENTIFICATION

NAMES: AMAZON SELECT RECYCLED LATEX PAINT; AMAZON BASIC RECYCLED LATEX PAINT  
U.S. DOT SHIPPING DESCRIPTION: Non-Regulated

---

## SECTION 2 – HAZARDS IDENTIFICATION



### WARNING

**Hazard Statement:**

Causes Mild Skin and Eye Irritations

**Precautionary Statements:**

Wear Eye and Face Protection

Eye Contact: Rinse Cautiously With Water for 15 Minutes

Skin Contact: Wash Thoroughly With Soap and Water

If Eye or Skin Irritation Persist: Get Medical Advice/Attention

For Additional Safety Information Please Consult the SDS For This Product

**KEEP OUT OF REACH OF CHILDREN**

HMIS CODES: HEALTH = 1; FIRE = 0; REACTIVITY = 0; PPE LEVEL = E

---

## SECTION 3 - HAZARDOUS INGREDIENTS

Ingredient	CAS No.	WT %	ACGIH OSHA EXPOSURE LIMITS					
			TLV/TWA	TWA		STEL		VAPOR PRESS
			ppm	ppm	mg/M <sup>3</sup>	ppm	mg/M <sup>3</sup>	
Ethylene Glycol	00107-21-1	0-5%				50	125	0.1 @ 68 F
Propylene Glycol	00057-55-6	0-5%						0.1 @ 68 F
Texanol Ester Alcohol	25265-77-4	0-5%						0.1 @ 68 F

NOTE: This product consists primarily of post-consumer recyclable latex paints that were produced by various manufacturers. Composition of finished product may vary with feedstocks.

---

## SECTION 4 – FIRST AID MEASURES

**INHALATION:** If affected by inhalation of vapor, move victim to fresh air. If not breathing, apply artificial respiration and call emergency medical care.

**EYE CONTACT:** For eye contact, flush eyes with fresh water for at least 15 minutes. If irritation persists, seek medical attention.

**SKIN CONTACT:** For skin contact, wash thoroughly with soap and water. Remove any contaminated clothing.

**INGESTION:** If swallowed, have victim drink enough fresh water to ensure dilution. Call emergency medical care.

---

## **SECTION 5 -FIRE FIGHTING MEASURES**

**FLAMMABILITY CLASSIFICATION:** N/A

**FLASH POINT:** N/A    **LEL:** N/A    **UEL:** N/A

**EXTINGUISHING MEDIA:** Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Liquid material is non-combustible, but dried films are capable of supporting combustion when in contact with open flames. Closed containers can develop internal pressure and may rupture when subjected to extreme heat.

**SPECIAL FIREFIGHTING PROCEDURES:** Use self-contained breathing apparatus in confined spaces. Observe recommended procedures for handling ordinary combustible materials.

---

## **SECTION 6 –ACCIDENTAL RELEASE MEASURES**

**STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED:** Dike and absorb spilled liquid with inert material such as clay granules, sand, earth, or sawdust. Use rags to clean up small amounts of spilled material.

---

## **SECTION 7 – HANDLING AND STORAGE**

**PRECAUTIONS FOR HANDLING AND STORAGE:** Keep containers closed when not in use. Do not handle or store near heat, flame, or strong oxidizers, acids and alkalis. Store in cool, well-ventilated area. Rotate stock, use older material first. Inspect all containers for leaks.

---

## **SECTION 8 – EXPOSURE CONTROLS /PERSONAL PROTECTION**

**VENTILATION:** For interior use, general mechanical ventilation may be sufficient to disperse vapor. Otherwise, open doors and windows or use portable fans to provide local exhaust.

**RESPIRATORY PROTECTION:** For spray application, use particulate filter mask to avoid breathing spray mist. Exposed persons with unusual allergic sensitivity may need organic vapor respirator (NIOSH/MSHA TC 23C or equivalent).

**EYE PROTECTION:** Use safety glasses, goggles, or face shield to protect eyes.

**PROTECTIVE GLOVES:** Use waterproof gloves (e.g., latex, vinyl, rubber, neoprene) to avoid skin contact.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Waterproof head covering and general protective clothing are recommended for protection as necessary.

**WORK/HYGIENIC PRACTICES:** Wash hands and face before eating.

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

**BOILING RANGE:** 200-225.F

**EVAPORATION RATE:** Slower Than Ether.

**SPECIFIC GRAVITY (H<sub>2</sub>O=1):** 1.4

**VAPOR DENSITY:** Heavier Than Air.

**SOLUBILITY IN WATER:** Partly soluble.

**VOLATILE VOLUME:** 60%

**APPEARANCE AND ODOR:** Liquid dispersion (various colors) with mild latex and ammonia odor.

---

## **SECTION 10 – STABILITY AND REACTIVITY**

**STABILITY:** Stable.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion can produce carbon monoxide and/or carbon dioxide.

**CONDITIONS TO AVOID:** Avoid storage or use at temperatures below 40.F. Avoid freezing.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Avoid water-reactive materials, strong oxidizers, acids and alkalis.

---

## **SECTION 11 –TOXICOLOGICAL INFORMATION**

### **POTENTIAL ROUTES OF ENTRY / SIGNS AND SYMPTOMS OF EXPOSURE**

**INHALATION:** Exposure to high vapor concentration may irritate mucous membranes and respiratory tract. Extreme overexposure may produce dizziness, headache, and nausea.

**EYE CONTACT:** Direct contact may cause eye irritation, redness, and tearing.

**SKIN CONTACT:** Prolonged contact may cause transient reddening of the skin.

**SKIN ABSORPTION:** Available information provides no evidence of adverse effects.

**INGESTION:** May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** Pre-existing eye, skin, and respiratory system disorders, and unusual allergic sensitivity.

**CHRONIC OR DELAYED HEALTH HAZARDS:** Available information provides no evidence of chronic or delayed health hazards associated with exposure to this product.

**CARCINOGENICITY:** NTP: NO. **IARC MONOGRAPHS:** NO. **OSHA REGULATED:** NO. **PROP 65:** NO.

---

## **SECTION 12 –ECOLOGICAL INFORMATION**

No toxicology testing results on aquatic or terrestrial organisms reported.

## **SECTION 13 –DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** Collect contaminated absorbent material and rags into a suitable container and dispose in accordance with all applicable local, state, and federal regulations.

---

## **SECTION 14 -TRANSPORTATION INFORMATION**

**SHIPPING REQUIREMENTS:** Products covered by this MSDS are not subject to DOT, IATA/ICAO, or IMO/IMDG transportation regulations. Acceptable for air transport as non-hazardous goods.

---

## **SECTION 15 –REGULATORY INFORMATION**

Contains less than 150 grams/liter of VOCs (as coating) per SCAQMD regulations.

---

## **SECTION 16 –OTHER INFORMATION**

**LATEST REVISION:** 9/25/2015

**STORGE AND USE INSTRUCTIONS:** Do not store in areas subject to freezing temperatures. Keep above 40.F at all times. Use only with adequate ventilation or protection. Avoid breathing spray mist or vapor. Do not ingest. Avoid contact with skin. Close container after each use. Keep out of reach of children.

**DISCLAIMER:** THE INFORMATION CONVEYED IN THIS SDS, ALTHOUGH OBTAINED FROM SOURCES CONSIDERED RELIABLE, IS FURNISHED BY AMAZON ENVIRONMENTAL INC. WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.