

PRODUCT INFORMATION
Amazon Select™ Interior/ Exterior Recycled Paint

Manufactured by:
Amazon Environmental, Inc.,
Riverside, CA Phone: 1-951-588-0206
Fridley, MN Phone: 1-763-572-0800
Sacramento, CA Phone: 1-916-922-0206

DESCRIPTION: Amazon Select is an interior/exterior latex paint for use on properly prepared drywall, masonry, wood, and metal. This recycled product is made with 80-99% post-consumer paint and offers an affordable alternative.

SPECIFICATIONS

SOLVENT TYPE

Waterborne

RESIN TYPE

Acrylic copolymer

FINISHES

Low-Sheen, Eggshell, Semi-gloss

COLOR

Various:

VISCOSITY @ 70 F (25 C)

80-105 KU

MAXIMUM VOC CONTENT

100 g/L

SOLIDS BY VOLUME

30-40%

SOLIDS BY WEIGHT

40-55%

WEIGHT PER GALLON

10.0 lbs. Minimum

COMPOSITION BY WEIGHT

This product consists primarily of post consumer recyclable latex paints. Composition of finished product may vary with feedstock.

RECOMMENDED FILM THICKNESS PER COAT

Wet: 4.3-5.0 mils Dry: 1.5 mils

RECOMMENDED COVERAGE PER COAT

250-350 sq. ft. per gallon, depending on surface conditions.

AVERAGE DRY TIME @ 77 F (25 C)

To touch: 30-60 minutes

Recoat: 2-4 hours

APPLICATION EQUIPMENT

Brush, roller, airless spray

PACKAGING

One-gallon, five-gallon containers

SURFACE PREPARATION

All surface must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, high-pressure washing or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should be sanded, cleaned, and spot primed with a suitable primer or sealer. If efflorescence exists, remove all noticeable deposits and prime the entire surface with a suitable primer.

SPECIAL INSTRUCTIONS

Amazon Select meets performance specifications for recycled latex paint. Do not apply when the air or surface temperature is below 50F. If spraying, recommend using a 0.019-inch orifice or larger, strainer, and clean in-filter regularly.

THINNING RECOMMENDATIONS

Designed to be applied at package consistency. Thinning is not recommended.

CLEAN UP

Warm, soapy water